

CHECKLIST FOR TILED AND PITCHED ROOFS

Quick guide:

1. Please fill out the form as completely as possible DIGITALLY (on screen) and save the file locally.
2. Open a new email in your email programme or the online environment of your email provider.
3. Send an email to info@profiness.de and attach the saved checklist.
If required, you can attach further information or attachments (e.g. illustration of the module assignment) to the email.

customer address		project location (if different location)	
name	<input type="text"/>	name	<input type="text"/>
street	<input type="text"/>	street	<input type="text"/>
city	<input type="text"/>	city	<input type="text"/>
phone	<input type="text"/>	phone	<input type="text"/>
building / location data			
roof pitch degree	<input type="text"/>	height of roof m	<input type="text"/>
		verge length m	<input type="text"/>
		building length m	<input type="text"/>
terrain height m	<input type="text"/>		
In case of above-rafter insulation: Distance from the support point of the roof hook to the screw-in point on the rafter <input type="text"/>			
wind load kN/m ²	<input type="text"/> *	snow load kN/m ²	<input type="text"/> *
		* Mandatory information for enquiries outside Germany	roof type <input type="text"/>
solar panel data			
quantity	<input type="text"/>	panel orientation	<input type="text"/>
length mm	<input type="text"/>	width mm	<input type="text"/>
		height mm	<input type="text"/>
		weight kg	<input type="text"/>
tiled roof			
distance between the rafters cm	<input type="text"/>	roof hook	<input type="text"/>
rafter dimension width x height in cm		additional comments:	<input type="text"/>
cup overlap due to hook length in cm	<input type="text"/>		
	standard hook length approx. 11cm, old. 16cm possible		
suitable bracket height in mm (results from batten height, pan thickness and 5mm safety distance) <input type="text"/>			
sketch			
Please sketch the planned array layout in the following grid or send us an layout plan!			