

CHECKLIST FOR TILED AND PITCHED ROOFS

customer address		project location (if different location)	
name	<input type="text"/>	name	<input type="text"/>
street	<input type="text"/>	street	<input type="text"/>
city	<input type="text"/>	city	<input type="text"/>
phone	<input type="text"/>	phone	<input type="text"/>

building / location data			
roof pitch degree	<input type="text"/>	height of roof m	<input type="text"/>
		verge length m	<input type="text"/>
		building length m	<input type="text"/>
terrain height m	<input type="text"/>		
In case of above-rafter insulation: Distance from the support point of the roof hook to the screw-in point on the rafter <input type="text"/>			
wind load kN/m ²	<input type="text"/> *	snow load kN/m ²	<input type="text"/> *
* Mandatory information for enquiries outside Germany			roof type <input type="text"/>

solar panel data			
quantity	<input type="text"/>	panel orientation	<input type="text"/>
length mm	<input type="text"/>	width mm	<input type="text"/>
		height mm	<input type="text"/>
		weight kg	<input type="text"/>

tiled roof			
distance between the rafters cm	<input type="text"/>	roof hook	<input type="text"/>
rafter dimension width x height in cm		additional comments:	<input type="text"/>
cup overlap due to hook length in cm	<input type="text"/>		
		standard hook length approx. 11cm, old. 16cm possible	
suitable bracket height in mm (results from batten height, pan thickness and 5mm safety distance)			<input type="text"/>

sketch
<p>Please sketch the planned array layout in the following grid or send us an layout plan!</p> <div style="border: 1px solid #ccc; height: 250px; width: 100%;"></div>